

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization International Bureau



(43) International Publication Date  
30 June 2005 (30.06.2005)

PCT

(10) International Publication Number  
WO 2005/059859 A1

(51) International Patent Classification<sup>7</sup>: G08C 17/00, G01N 27/26, 33/02

(21) International Application Number: PCT/FI2004/050188

(22) International Filing Date: 16 December 2004 (16.12.2004)

(25) Filing Language: Finnish

(26) Publication Language: English

(30) Priority Data: 20031861 18 December 2003 (18.12.2003) FI


(71) Applicant (for all designated States except US): UPM-KYMMENE CORPORATION [FI/FI]; Eteläesplanadi 2, FI-00130 HELSINKI (FI).

(72) Inventors; and

(75) Inventors/Applicants (for US only): VARPULA, Timo [FI/FI]; Suuvaopku 7 A, FI-01660 VANTAA (FI). SEPPÄ, Heikki [FI/FI]; Partiotie 26, FI-00370 HELSINKI (FI). SAARI, Juha-Matti [FI/FI]; Rautakiskonkuja 4 B 17, FI-02650 ESPOO (FI).

(74) Agent: GUSTAFSSON, Helmer; UPM-Kymmene Corporation, P.O. Box 40, FI-37601 VALKEAKOSKI (FI).

(54) Title: A RADIOFREQUENCY BASED SENSOR ARRANGEMENT AND A METHOD



(57) Abstract: The invention relates to a sensor arrangement and a method for a sensor arrangement (1, 3, 5) remotely readable by radio frequencies. The sensor arrangement comprises an LC resonator (3, 5) which comprises a capacitor (3) and a coil (5), and a sensor element (1) coupled to the LC resonator (3, 5) whose properties change as a function of a measurable quantity. A sensor element (1) according to the invention does not form a direct galvanic contact with the LC resonator (3, 5), rather the coupling is implemented capacitively or inductively.